

# BOCHINI

## TENSILE STRUCTURE FABRIC - TYPE 0

### PVC COATED FABRIC

#### APPLICATIONS

Lightweight tensioned structures, marquees and tents

Roll Width	300cm	
Roll Length	65 metres	
Nominal Weight	580gsm	
Fabric Type	PVC coated material with woven polyester scrim	
Base Fabric	1000D low wick polyester	
Fabric Density	8 x 8 yarns per cm	
Fabric Finish	Glossy, both sides PVDF lacquer	
Treatment	Weldable PVDF lacquer on both sides Fire Retardant B1 (AS 1530.2-1999 & AS 1530.3-1999) Fungicide treated Anti-mildew	
Colours	White, Cream, Champagne, Paperbark*, Royal Blue, Navy, Shale Grey*, Mid Grey, Ironstone*, Monument* & Black	
Tensile Strength	Warp: 2300 N/50mm Weft: 2300 N/50mm	
Adhesion	100N / 50mm	
Elongation at break	Warp: 22% Weft: 22%	
Tear Strength	Warp: 230N Weft: 230N	
Features	10 year warranty Lightweight Waterproof	PVDF lacquer both sides UV stabilised Low maintenance

\*Inspired by COLORBOND®



Colorbond®

